


270 Series

Vitreous Enamel Power



See page 36
for mounting
hardware

FEATURES

- Terminals suitable for soldering or bolt connection.
- High wattage applications.
- Rugged lead free vitreous enamel coating.
- Flame resistant coating.
- All-welded construction.
- RoHS compliant product available. Add "E" suffix to part number to specify.

SPECIFICATIONS

Material

Coating: Lead free vitreous enamel. Very large models (750 watts and up) are supplied in Silicone Ceramic. Also available in low-cost Centohm coating; Consult factory.

Core: Tubular ceramic.

Terminals: Solder coated radial lug. RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu

Derating: Linearly from 100% @ +25°C to 0% @ +350°C.

Electrical

Tolerance:

±5% 1Ω and over (J)
±10% under 1Ω (K)

Power rating: Based on 25°C free air rating.

Overload: 10 times rated wattage for 5 seconds.

Temperature coefficient:

1 to 20Ω: ±400 ppm/°C.
Above 20Ω: ±260 ppm/°C

Dielectric withstanding voltage:

1000 VAC: 12 to 100 watt rating.
3000 VAC: 175 to 225 watt rating (Measured from terminal to mounting bracket)

To calculate max. amps: use the formula $\sqrt{P/R}$

Series	Wattage	Ohms	Dimensions (in. / mm)			Core Code	Voltage	Standard Terminal
			L	D	C			
L12	12	0.1-51K	1.75 / 44.4	0.313 / 7.94	0.188 / 4.76	D	565	57
L25	25	0.15-100K	2.0 / 50.8	0.562 / 14.3	0.313 / 7.94	K	625	40
L50	50	0.38-260K	4.0 / 101.6	0.562 / 14.3	0.313 / 7.94	K	1625	40
L100	100	0.23-101K	6.5 / 165.1	0.750 / 19.1	0.50 / 12.7	M	2845	40
L175	175	0.13-101K	8.5 / 215.9	1.125 / 28.6	0.75 / 19.1	P	3595	46
L225	225	0.16-129K	10.5 / 266.7	1.125 / 28.6	0.75 / 19.1	P	4595	46
L500	500	0.38-218K	12.0 / 304.8	2.50 / 63.5	1.75 / 44.5	S	4970	45
L1000	1000	0.69-392K	20.0 / 508.0	2.50 / 63.5	1.75 / 44.5	S	8900	45

Non-Inductive versions available; Other sizes available; Also available in low cost Centohm or Silicone coating; Consult Ohmite.
* Maximum Voltage is based on Ohm's Law $[V=\sqrt{P \cdot R}]$ as limited by the resistance value of specified product

Select 270 Type fixed resistors for applications requiring wattage ratings from 12 to 1000 watts.

The 270 Type resistors are equipped with lug terminals suitable for soldering or sturdy bolt connection. When secure mounting is required, the hollow core of these resistors permit fastening with spring-type brackets, thru bolts or thru bolts with slotted-steel brackets.

Suitable for rugged applications, the 270 Type resistors feature all-welded construction and durable lead free vitreous enamel coating. Mounting brackets not included with resistors.

ORDERING INFO

Series	Non-inductive Blank = Standard N = Non-inductive	RoHS Compliant
L	25	J
Coating	Wattage	Tolerance
Blank = Vitreous	Blank = Standard	J = 5%
C = Centohm	250 = 250 Ω	K = 10%
S = Silicone	1K0 = 1,000 Ω	
	25K = 25,000 Ω	
	25K5 = 25,500 Ω	

MADE-TO-ORDER PARTS

Non-inductive Blank = Standard N = Non-inductive	Core Diameter See "Core and Terminal Selection"	RoHS Compliant
270	50	K
Coating	Wattage	Ohms
270 = Vitreous	Blank = Standard	R500 = 0.500 Ω
470 = Silicone Ceramic	250 = 250 Ω	1R00 = 1 Ω
	1K00 = 1,000 Ω	25K0 = 25,000 Ω
	25K5 = 25,500 Ω	

Terminal Type
See "Resistor Terminals
for Tubular Cores"

See website for
custom core and
terminal info

Power limitations for high resistance values: When resistance exceeds the resistance values listed, derate the Power Rating by 25% to improve reliability:

Power rating	Resistance value	No power derating necessary for ratings higher than 100W.
12W	3,900Ω	
25W	12,000Ω	
50W	35,000Ω	
100W	75,000Ω	

STANDARD PART NUMBERS FOR 270 SERIES

Ohmic value		12 Watt		Ohmic value		12 Watt		Wattage										Wattage									
12 Watt		12 Watt		12 Watt		12 Watt		Wattage										Wattage									
0.51	✓	L12JKR51E	180	✓	L12J180E	270	✓	L12J270E	25	50	100	175	225	500	1000			25	50	100	175	225	500	1000			
1	✓	L12J1R0E	330	✓	L12J330E	390	✓	L12J390E	L25J	L50J	L100J	L175J	L225J	L500J	L1000J			L25J	L50J	L100J	L175J	L225J	L500J	L1000J			
3.3	✓	L12J3R3E	470	✓	L12J470E	560	✓	L12J560E	1	2	3	4	5	10	15	25	50	1	2	3	4	5	10	15	25	50	100
4.7	✓	L12J4R7E	1000	✓	L12J1K0E	1200	✓	L12J1K2E	2	3	4	5	10	15	25	50	100	2500	3000	3500	4000	5000	6000	7500	10000	12000	15000
10	✓	L12J10RE	1500	✓	L12J1K5E	1500	✓	L12J1K5E	10	15	25	50	75	100	125	150	200	2000	2500	3000	3500	4000	5000	6000	7500	10000	12000
12	✓	L12J12RE	2200	✓	L12J2K2E	2700	✓	L12J2K7E	15	25	50	75	100	125	150	200	250	2500	3000	3500	4000	5000	6000	7500	10000	12000	15000
15	✓	L12J15RE	4700	✓	L12J4K7E	4700	✓	L12J4K7E	25	50	75	100	125	150	200	250	500	5000	6000	7500	10000	12000	15000	20000	25000	30000	35000
22	✓	L12J22RE	10000	✓	L12J10KE	18000	✓	L12J18KE	75	100	125	150	200	250	500	750	1000	10000	12000	15000	20000	25000	30000	35000	40000	50000	60000
27	✓	L12J27RE	22000	✓	L12J22KE	22000	✓	L12J22KE	100	125	150	200	250	500	750	1000	1500	15000	20000	25000	30000	35000	40000	50000	60000	75000	100000
33	✓	L12J33RE	51000	✓	L12J51KE				250	500	750	1000	1500	2000	2500	5000	7500	75000	100000	150000	200000	250000					
47	✓	L12J47RE																									
68	✓	L12J68RE																									
82	✓	L12J82RE																									
100	✓	L12J100E																									
150	✓	L12J150E																									

✓ = Standard values; check availability using the worldwide inventory search at www.ohmite.com

Red outlined values supplied in Silicone-Ceramic coatings instead of vitreous enamel.