

NOTES:

1. MOUNTING: Panel mounting hole .171" (4.34mm) Diameter
Litepipe from .200" to .500" use grommet retainer RTN 150
Litepipe from .500" to 2.00" the spring retainer RTN 250 is recommended for rigidity
2. Standoff used to adjust the height of a standard LED above the PCB to maintain a maximum .050" clearance between Litepipe and LED.
3. U.S. & Foreign Pat Issued & Pend.

REVISIONS				
ECN #	REV	DESCRIPTION	DATE	INITIALS
	N/A	INITIAL RELEASE	8/25/98	JS
	1	UPDATE DWG FORMAT	12/15/08	JG
	2	REVISE .170" DIMENSION TOLERANCES	3/11/09	AZ
	001	REVISED PER ECR111009AZ01	4/23/10	KH



SECTION A-A



ORDERING CODE: LPC **XXX** CTP

LENGTH CODE (Min 020=.200" / Max 200=2.000")															
020	038	056	074	092	112	135	157	180							
022	040	058	076	094	115	137	160	182							
024	042	060	078	096	117	140	162	185							
026	044	062	080	098	120	142	165	187							
028	046	064	082	100	122	145	167	190							
030	048	066	084	102	125	147	170	192							
032	050	068	086	105	127	150	172	195							
034	052	070	088	107	130	152	175	197							
036	054	072	090	110	132	155	177	200							
SPECIAL LENGTHS UPON REQUESTS															

COLOR	
CTP	CLEAR



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		MATERIAL ACRYLIC (OPTICAL GRADE) UL 94-HB		VISUAL COMMUNICATIONS COMPANY, INC. 190 Bosstick Boulevard, Suite 101 San Marcos, CA 92069 USA Phone (760) 560-1300 Fax (760) 560-1301 email vccsales@vccilite.com	
ANGLES ±1°	DECIMALS .X ±.020 .XX ±.010 .XXX ±.005	FINISH SEE NOTES		TITLE: CLIPLITE 4MM LITEPIPE VERTICAL	
THIRD ANGLE PROJECTION		APPROVAL		DATE	
DRAWN K.Howard		4/23/10		SIZE DWG. NO.	
CHECKED DPZ		5/4/10		SCALE: 8:1	
DO NOT SCALE DRAWING		SHEET 1 OF 1		REV 001	